Hand-held Wireless Programmable Touch Screen





Instruction

Desktop wireless full-color touch screen, compatible with newgeneration of PGMIII programmable mainframe, with wireless transmission distance of 50m, support 16:9 high resolution color (18bit color depth) wide screen display, with the advantage of easyto-use, solid, durable and fast-reacting.

Features

- Support wireless transmission in accessible area as far as 50M
- Support TFT true-color LCD, support 16:9 high resolution color (18bit color depth) wide screen display
- Self-customized operation interface, with common image formats like PNG and JPG, graphic interface support text, 3D button, multi-form button, irregular button effect, vivid and beautiful user interface
- Rich optional button sound types
- Adopt intelligent chipset with CPU at 667MHz
- Slightly touch screen to realize free control
- Support hand-held mobile use
- Adopt high-end TouchLens technique, with fashionable and beautiful appearance design.

Specifications

| Type | | CR-Wireless G7C | | CR-Wireless G7pip |
|---|-----------------------------|--|----------------------|-----------------------|
| Display mode | | TFT LCD full color | | TFT LCD full color |
| Resolution | | 800 x 400 | | 800 x 400 |
| Control mode | | Wireless | | Wireless |
| Size | | 8-inch | | 8-inch |
| Application range | | Connecting to CR-PGMIII control system | | |
| PIP switching | | No | | Yes |
| Communication po | | ort USB port | | USB port |
| Memory | | 2G | | 2G |
| Wireless transmission frequ | | ion frequency | 433MHz | 433MHz/5.8GHz(video) |
| Remote control distance 50m(accessible) | | | 50m/∠30m(accessible) | |
| External power supply DC | | 012V/3.3A | DC12V/3.3A | |
| Battery | Battery Capacity | 7.4\ | //4400mAh | 7.4V/4400mAh |
| | Recharge saturation time 5h | | 5h | |
| | Recharging temp |). | 0℃-50℃ | 0℃-50℃ |
| | Battery Spec. | | Li-ion rech | argeable battery 7.4V |



5-view diagram Outline dimension(Unit:mm)

